

LIS009543465B2

### (12) United States Patent

Suzuki et al.

# (10) Patent No.: US 9,543,465 B2 (45) Date of Patent: Jan. 10, 2017

## (54) METHOD FOR MANUFACTURING LIGHT EMITTING DEVICE

(71) Applicant: NICHIA CORPORATION, Anan-shi,

Tokushima (JP)

(72) Inventors: Ryo Suzuki, Anan (JP); Yoshikazu

Takeuchi, Komatsushima (JP); Hirokazu Sasa, Anan (JP)

(73) Assignee: NICHIA CORPORATION, Anan-shi

(JP)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/716,451

(22) Filed: May 19, 2015

#### (65) Prior Publication Data

US 2015/0340546 A1 Nov. 26, 2015

#### (30) Foreign Application Priority Data

May 20, 2014	(JP)	2014-104248
Jan. 30, 2015	(JP)	2015-017629

(51) **Int. Cl. H01L 33/00** 

(2010.01)

(52) **U.S. Cl.** 

CPC ..... *H01L 33/0079* (2013.01); *H01L 2933/005* (2013.01); *H01L 2933/0041* (2013.01)

#### (58) Field of Classification Search

None

See application file for complete search history.

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

2008/0036362 A1 2010/0320479 A1*		Tanimoto et al. Minato H01L 33/56
		257/88
2011/0233586 A1	9/2011	Kojima et al.
2012/0248484 A1	10/2012	Sato et al.
2014/0080235 A1	3/2014	Yajima et al.
2015/0021642 A1	1/2015	Nakabayashi

#### FOREIGN PATENT DOCUMENTS

JP	2007-109822 A	4/2007
JP	2008-521210 A	6/2008
JP	2010-251807 A	11/2010
	(Cont	inued)

#### OTHER PUBLICATIONS

Unpublished U.S. Appl. No. 14/568,256 by Takuya Nakabayashi et al., filed Dec. 12, 2014, entitled Light Emitting Device.

Primary Examiner — Armando Rodriguez (74) Attorney, Agent, or Firm — Global IP Counselors, LLP

#### (57) ABSTRACT

A method for manufacturing a light emitting device has: preparing a base body which comprises a pair of connection terminals; preparing a light emitting element which includes a substrate, a semiconductor laminate that is laminated on the substrate, and a pair of electrodes formed on the surface of the semiconductor laminate; joining the electrodes of the light emitting element to the connection terminals of the base body; covering the light emitting element with a sealing member; and removing at least a part of the sealing member and a part of the substrate of the light emitting element from the opposite side from the base body so that an upper surface of the sealing member is lower than an upper surface of the substrate of the light emitting element.

#### 11 Claims, 10 Drawing Sheets

